

Recommended FLEXITILE Installation Systems

For other suitable options & complete installation details, visit www.flextile.net

PRODUCT	GLAZED WALL TILE		PORCELAIN TILE WALL		PORCELAIN TILE FLOOR	
	Interior	Exterior	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• DuoFlex 90 Adhesive • 66 FlexLite Mortar	n/a	• 66 FlexLite Mortar • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar Syst.	• 50 PM Mortar • 52 Versatile PM Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar Syst.
GROUT	• 500 PM Unsanded Grout • 1600 UPG	n/a	• 600 PM Sanded Grout • 1600 UPG	• 600 PM Sanded Grout • 1600 UPG	• 600 PM Sanded Grout • 1600 UPG • FlexEpoxy 100	• 600 PM Sanded Grout • 1600 UPG
CAULKING	UP Caulk - Unsanded	n/a	UP Caulk - Sanded	UP Caulk - Sanded	UP Caulk - Sanded	UP Caulk - Sanded

SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

* For a complete listing of FLEXITILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



"MORE" Surface Care Product Guide

Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

*Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.

