

Recommended FLEXTILE Installation Systems

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• 66 FlexLite	n/a	n/a	n/a
GROUT	• 500 PM Unsanded • 1600UPG PM Grout	n/a	n/a	n/a
CAULKING	Ultra Performance (colour-matched to grout)	n/a	n/a	n/a

SURFACE PREPARATION (If Required)

- · Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- · Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

^{*} For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



"MORE" Surface Care Product Guide

N. N. N. SHIP N. N. SHI			
Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

^{*}Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.











