

## **Recommended FLEXTILE Installation Systems**

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• 66 FlexLite • 55LHT Mortar • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System • 58XT Fast Set Latex Mortar Syst.	• 55LHT Mortar • 56SR LHT Mortar • 5400 Maxi-Flex	• 5400 Maxi-Flex • 51/44 Latex Mortar System • 58XT Fast Set Latex Mortar Syst.
GROUT	• 500 PM Unsanded • 600 PM Sanded • 1600UPG PM Grout	• 1600UPG PM Grout	• 600 PM Sanded • 1600UPG PM Grout • FlexEpoxy 100 Epoxy Grout	• 1600UPG PM Grout
CAULKING	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)

## SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- · Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

<sup>\*</sup> For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



## "MORE" Surface Care Product Guide

· · · · · · · · · · · · · · · · · · ·			
Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

<sup>\*</sup> Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.







www.olympiatile.com







