

PRODUCT	GLAZED WALL TILE		GL. PORCELAIN WALL		GL.PORCELAIN FLOOR	
	Interior	Exterior	Interior	Exterior	Interior	Exterior
<b>TILE BOND COAT</b>	66 FlexLite Mortar 56SR LHT Mortar	n/a	66 FlexLite Mortar 56SR LHT Mortar	5400 Maxi-Flex 51/44 Latex Mortar	61 Full Covge. Mortar 56SR LHT Mortar	5400 Maxi-Flex 51/44 Latex Mortar
<b>GROUT</b>	500 PM Unsanded Grout 1600 UPG PM Grout	n/a	600 PM Sanded Grout 1600 UPG PM Grout	600 PM Sanded Grout 1600 UPG PM Grout	600 PM Sanded Grout 1600 UPG PM Grout FlexEpoxy 100 Epoxy	600 PM Sanded Grout 1600 UPG PM Grout
<b>CAULKING</b>	UP Caulk - Unsanded	n/a	UP Caulk - Sanded	UP Caulk - Sanded	UP Caulk - Sanded	UP Caulk - Sanded

### SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

\* For a complete listing of FLEX TILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit [www.flextile.net](http://www.flextile.net)



## "MORE" Surface Care Product Guide

Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

\* Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.

