

Recommended FLEXTILE Installation Systems

For other suitable options & complete installation details, visit www.flextile.net

| PRODUCT | WALL APPLICATION | | FLOOR APPLICATION | |
|-------------------|--|---|--|---|
| | Interior | Exterior | Interior | Exterior |
| TILE BOND COAT | • 66 FlexLite PM Mortar • 55 LHT Mortar • 56SR LHT Mortar | • 5400 Maxi-Flex • 51/44 Latex Mortar System | • 55LHT LHT Mortar • 56SR LHT Mortar | • 5400 Maxi-Flex • 51/44 Latex Mortar System |
| GROUT | 500 PM Unsanded600 PM Sanded1600UPG PM Grout | • 600 PM Sanded • 1600UPG PM Grout | • 600 PM Sanded • 1600UPG PM Grout • FlexEpoxy 100 Epoxy Grout | • 600 PM Sanded • 1600UPG PM Grout |
| CAULKING | Ultra Performance (colour-matched to grout) | Ultra Performance (colour-matched to grout) | Ultra Performance (colour-matched to grout) | Ultra Performance (colour-matched to grout) |

SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- · Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

^{*} For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



"MORE" Surface Care Product Guide

| HIGHE | | | | |
|----------------------------------|--|---------------------|---|--|
| Task | Product Recommendation | Dilution with Water | Frequency | |
| Grout Sealing | MORE™ Grout, Ceramic & Porcelain Sealer | Ready to use | Commercial: 1-3 Years Residential: 5-8 Years | |
| Daily Maintenance | MORE™ Stone and Tile Cleaner | 1 : 128 Ratio | Daily | |
| Deep Cleaning | MORE™ Alkaline Cleaner | 1 : 4 Ratio | As Needed | |
| Grout Haze- Cementitious | MORE™ Acidic Cleaner | 1 : 4 Ratio | As Needed | |
| Grout Haze - Epoxy / Urethane | MORE™ Coating Stripper* | Ready to use | As Needed | |

stAlways test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.











