

## ASTRUM SERIES

## Tests Performed -- Results Conform

Test	Standard Used	Min. Requirements	Results
Water Absorption	ISO 10545-3	< 0.5%	Conforms
Bending / Breaking Strength	ISO 10545-4	>1300N	Conforms
Dynamic Coefficient of Friction	ANSI A137.1/2012	0.42	Conforms
Chemical Resistance	ISO 10545-13	min. UB	Conforms
Frost Resistance	ISO 10545-12	Required	Conforms
Stain Resistance	ISO 10545-14	> Class 3	Conforms

Technical data is supplied by the manufacturer and is subject to change at any time. Olympia does not provide warranties as to the specifications of any product.

## Colour Variation



## Member



Member of Canada  
Green Building  
Council



Member of U.S.  
Green Building  
Council

TTMAC ACTTM

The Terrazzo, Tile, and  
Marble Association of  
Canada



Ceramic Tile  
Distributors of  
America (CTDA)



Marble Institute  
of America

For information concerning LEED, please  
contact our Sales Representative

## Examples of Recommended Applications

Residential Commercial



Indoor



Outdoor



Wall



Floor



## Packing Details

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
24" x 24" Cross cut, Matte	3	11.62	48.48	40
24" x 48" Vein cut, Matte	2	15.50	66.14	35

olympiatile+stone®

