

Recommended FLEXTILE Installation Systems

For other suitable options & complete installation details, visit www.flextile.net

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• 66 FlexLite • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System	• 56SR LHT Mortar • 5400 Maxi-Flex	• 5400 Maxi-Flex • 51/44 Latex Mortar System
GROUT	500 PM Unsanded600 PM SandedColourMax Plus Quartz	• 600 PM Sanded • 1600 RSG Fast Setting	• 600 PM Sanded • FlexEpoxy 100 Epoxy	• 600 PM Sanded • 1600 RSG Fast Set
CAULKING	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)

SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

^{*} For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



"MORE" Surface Care Product Guide

1110/116				
Task	Product Recommendation	Dilution with Water	Frequency	
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years	
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily	
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed	
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1:4 Ratio	As Needed	
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed	

^{*}Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.











